



V 1.1 - 082024

PeopleLink Impact Pro 20x Endpoint



PeopleLink Impact Pro is an endpoint device that delivers HD-quality audio/visuals even in low bandwidth. The in-built VPN feature provides required network security for all users. The device allows easy data and rich-media sharing with ease and can be easily integrated with standardized video systems and other hardware based endpoints with necessary licenses, making it exceptionally pocket-friendly.

PRODUCT FEATURES

- 20x Optical zoom lens
- Supports standard SIP and H.323
- Supports H.264 HP encoding
- Built-in VPN
- Built-in HD MCU function (optional)
- Supports Low bandwidth, high definition
- Remote, local recording, and broadcasting
- Embedded 8G EMMC storage space
- High network security

Technical Specifications:

Package Includes:

- 1 x HD Codec Built-in 20x Zoom HD PTZ Camera
- 1 x Omni-array Microphone
- 1 x Remote Control
- 1 x AC Power Adapter
- 1 x AC Power Cable
- 2 x HDMI cable (1.5m)
- 1 x User Manual (Quick Start, Quick installation Guide)
- 1 x XLR jack to 3.5mm jack cable

Bandwidth:

IP: 64KBPS - 8MBPS

Standards & Protocols:

ITU-T H.323, IETF SIP

Video Standards And Protocols

H.261, H.263, H.263+, H.263++, H.264, H.264 SVC, H.264 High Profile

Audio Standards And Protocols:

G.711, G.722, G.722.1*, G.722.1C*, AAC-LD, G.723.1, G.726, G.728, SILK

Dual Stream:

ITU-T H.239, BFCP

Other Standards

H.221, H.225, H.235, H.241, H.245, H.281, H.350, H.460, T.140, DTMF

Network Standards And Protocols

TCP/IP, DHCP, SSH, HTTP, HTTPS with SSL/TLS, RTP, RTCP, RFC3261, RFC3264, RFC2190, RFC3407, RFC2833, RFC4585 (RTP/AVPF), SNMP, ARP

Video Resolution:

1080P (optional), Guaranty bandwidth : 512Kbps

720P, Guaranty bandwidth : 384Kbps

4SIF/4CIF, Guaranty bandwidth : 128Kbps

SIF/CIF/QSIF/QCIF/SQSIF/SQCIF, Guaranty bandwidth: 64Kbps

Content Video Resolution

Input Resolutions:

VGA (640 x 480), SVGA (800 x 600), XGA (1024 x 768), WXGA (1280 x 768 & 1280 x 800), 1280 x 960, SXGA (1280 x 1024), 1360 x 768, 1366 x 768, 1440 x 900, XGA+ (1400 x 1050), 1600 x 900, 1600 x 1200, 1680 x 1050, 720p (1280 x 720), 1080p (1920 x 1080)

Coding/Decoding Resolutions:

800 x 600, 1024 x 768, 1280 x 1024, 1280 x 720, 1920 x 1080 (optional)

Output:

800 x 600, 1024 x 768, 1280 x 1024, 1280 x 720, 1920 x 1080

Dual Stream:

Dual 720P (1080P optional)

Built-in HD Camera:

Input: 720p (1080p optional)

Sensor: 2.07 million effective pixels, 1/2.7 inch CMOS

Lens: 20x optical zoom

Maximum horizontal viewing angle: 60.7 degrees

PTZ: horizontal +/-170 degrees, vertical -30~+90 degrees

Supports auto white balance, auto exposure, auto focus

Supports remote-camera control

Supports mirror/flip

10 presets

Other Video Features: PiP (Picture in Picture), PoP (Picture outside Picture)

Other Video Features:

PiP (Picture in Picture), PoP (Picture outside Picture)

Audio Features:

AEC (Acoustic Echo Cancellation)

AGC (Automatic Gain Control)

ANS (Acoustic Noise Suppression)

Lip synchronization

Security And Stability

Network:

FEC (Forward Error Correction)

ARQ (Automatic Repeat-request) etc.

Security

H.235 (AES) signaling and media stream encryption

Administrator password, SSH/HTTPS

Firewall Traversal

H.460.18/19, H.460.23/24, ICE

Bandwidth

64kbps ~ 8Mbps

Interfaces

Audio Input : 1 x 3.5mm line-in jack,
1 x 3.5mm mic-in jack

Audio Output : 1 x 3.5mm line-out jack,
1 x HDMI audio output

Video Input : 1 x HDMI, 2 x Built-in Camera

Video Output : 2 x HDMI

Communication Interface : 1 x RS232: 3 pin Phenix jack

USB Interface : 2 x USB 2.0 Host (support USB flash disk,
USB microphone, etc.)

ZHI : 1 x RJ45 : 10/100 Base-T

Application Features:

Approval And Compliance :

1000 local address book

Recommended Luminance : > 300 lux

Special Features :

Audio associated with presentation

Support "SameView"

Timing power on and power off

Automatic standby and wake up on incoming call

Support DNS SRV

Incoming call password

Asymmetric bandwidth

Built-in VPN

Automatic to get static NAT address

PIP : 1/16 picture size, optional position

Split output : Bi-screen and tri-screen display

Network address book

Support SDK API

Built-in MCU (optional)

Support web-based conference management

Support USB microphone

Remote Control : H.224, H.281

Remote upgrade by network

Wi-Fi (optional)

Physical Characteristics

Dimensions:

Codec dimensions (L x W x H):

240mm x 144mm x 160mm

Package dimensions (L x W x H):

285mm x 235mm x 230mm

Net weight : 1.7Kg

Package weight : 2.5Kg

Electrical :

Working voltage : AC 100V ~ 240V, DC 12V

Working frequency : 50/60Hz

Power consumption : 18W

Environmental Specification :

Operating temperature : 0°C to 40°C

Operating humidity : 10% to 80%

Non-Operating temperature : -40° to -70°C

Non-Operating humidity (non-condensing) : 0% to 95%


Peripheral noise : < 46 dBA SPL

Lowest luminance : 5 lux


Recommended luminance : > 300 lux

Approval and Compliance :

CCC, CE, RoHS, WEEE, FCC



Application Scenarios



Disclaimer:- Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.

ORDERING INFORMATION:

PeopleLink Impact Pro 20X : **PEP-PIS-HX-P-10**

PeopleLink Impact Pro 20X (1+3) : **PEP-PIS-HX-P-30**

LEARN MORE

For more information on **PeopleLink Impact Pro 20x Endpoint** [Click Here](#)

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers,
HITEC City, Hyderabad,
Telangana 500081, **India**
Phone: +91 9100123013
Email: vc@peoplelinkvc.com

International Contact Numbers

USA: +1 669-696-8383

Australia: +61 370 037070

France: +33 6 80 75 26 42

Middle East: +966 5300 19292

UK: +44 20 4571 5454

UAE: +971 4 3339082

Canada: +1 647-945-7373

Malaysia: +(6)018-2872188

New Zealand: +64-9-802-4666

Africa: +254 722 619 314

Tech Support

Toll Free: 1800 208 3399
customersupport@peoplelinkvc.com